# **RINNOVA PIASTRELLE** WHITE AND SHINY LIQUID FOR RECOVERING DISCOLORED TILE GROUT



## **PRODUCT DESCRIPTION**

White and shiny liquid for repairing discoloured tile grout. Ideal for restoring the original white colour of joints between tiles. With convenient sponge in the cap for easy application.

## **FIELD OF APPLICATION**

Suitable for restoring the original white colour of grout between tiles. A single treatment is sufficient to restore the original luster in joints.

## PROPERTIES

- · Ready to use
- · Easy to apply
- · Liquid
- · Powerful

## PREPARATION

**Working conditions:** Do not use in temperatures  $\leq +5^{\circ}$ C. **Preliminary surface treatment:** The joints to be treated should be dry and dust-free. If necessary, first degrease with a dilutent or with an ordinary detergent and let dry.

**Tools:** In the cap mounted sponge and a damp cloth.

# APPLICATION

#### **Directions for use:**

Put the sponge on the neck of the bottle. Shake bottle well before use. Transfer the liquid to the joints of the tiles by pressing in the bottle lightly. Wipe the sponge from the bottom up over the joint. Let dry for about 60 minutes, then wipe the joints with a damp cloth. Then keep the joints dry for at least 4 hours. **Stains/residue:** Clean the sponge after use with soap and water. **Points of attention:** After applying Bostik Rinnova Piastrelle, keep the joints

dry for at least 4 hours.

It is recommended not to apply Bostik Rinnova Piastrelle in areas with mould.

Do not swallow and keep out of the reach of children.

### CURE TIMES Dry/Cure time: approx. 24 hours

\* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

# **TECHNICAL PROPERTIES**

Moisture resistance: Good Temperature resistance: -20°C to +80°C

# **TECHNICAL SPECIFICATIONS**

Colour: White Viscosity: approx. 0 mPa.s., Liquid

# **STORAGE CONDITIONS**

At least 24 months after date of manufacture. Limited shelf life after opening. Store in properly sealed packaging in a dry place at between  $+5^{\circ}$ C and  $+25^{\circ}$ C.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.

309084 20161226