6303113 - BOSTIK STRISCIA SIGILLANTE BLISTER 38 MM X 3.35 M IT - D1808 (1808)

RISCIA SIGILLANTE ADHESIVE SEALING STRIP FOR A PERMANENTLY BEAUTIFUL AND WATERPROOF JOINT.



PRODUCT DESCRIPTION

Self-adhesive sealing strip for permanently beautiful and waterproof joints along baths, showers, sinks and floors. Easy to apply.

FIELD OF APPLICATION

Suitable for decorative sealing of joints along baths, showers, washbasins, countertops, sinks and floors.

PROPERTIES

- Immediate bonding
- · Easy to apply
- · Water resistant
- · Decorative
- · Permanently beautiful
- · Resistant to cleaning agents

PREPARATION

Working conditions: Only apply at temperatures between $+5^{\circ}$ C and $+40^{\circ}$ C. Preliminary surface treatment: Thoroughly clean the surface using an abrasive and carefully remove old sealant residue. Treat irregularities in the surface, such as deep tile joints, with a fine filler. Degrease the surface thoroughly with methylated spirits or ammonia (not white spirit!) and allow to dry properly

Tools: Scissors, cutter.

APPLICATION

Directions for use:

Cut the sealant strip to size, observing 10-15 mm clearance. Start with the longest joint. Fold double the strip along its entire length and pull back a part of the backing tape. Place the beginning of the strip on the joint and apply the strip while firmly pressing downward. Please note: do not stretch the strip as you press! Cut off the excess strip at the end of the joint. Make sure the strip adheres well everywhere (especially in the tile joints), then apply the other strip(s) in the same way. In corners, overlap strips. Cut the overlapping pieces from the corner at an angle (45°) and remove the pieces. Press the corner again firmly.

TECHNICAL PROPERTIES Water resistance: Very good

TECHNICAL SPECIFICATIONS

Colour: White Viscosity: approx. 0 mPa.s.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results ned and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed

5303 113 2016