

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- . 1.1 Product identifier
- . Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT
- . **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- . Application of the substance / the mixture Adhesive
- . 1.3 Details of the supplier of the safety data sheet
- . Manufacturer(1)/Supplier(2):

1

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- . Further information obtainable from: Bison QESH
- . **1.4 Emergency telephone number:** +31 88 3235700

SECTION 2: Hazards identification

- . 2.1 Classification of the substance or mixture
- . Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- 2.2 Label elements
- . Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

. Hazard pictograms





GHS07 GHS09

. Signal word Warning

(Contd. on page 2)

GB-EN

www.bostik.it 1/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 1)

. Hazard-determining components of labelling:

formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < = 700)

oxirane, mono[(C12-14-alkyloxy)methyl] derivates

. Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

==>> Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms





GHS07 GHS09

. Signal word Warning

. Hazard-determining components of labelling:

formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < = 700)

oxirane, mono[(C12-14-alkyloxy)methyl] derivates

. Hazard statements

H317 May cause an allergic skin reaction.

. Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

. 2.3 Other hazards

. Results of PBT and vPvB assessment

. **PBT:** Not applicable. **vPvB:** Not applicable.

GB-EN

(Contd. on page 3)

www.bostik.it 2/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

- . 3.2 Mixtures
- . Description: Adhesive

. Dangerous components:		
CAS: 9003-36-5 Reg.nr.: 01-2119454392-40	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	25-50%
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < = 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%
CAS: 68609-97-2 EINECS: 271-846-8 Reg.nr.: 01-2119485289-22	oxirane, mono[(C12-14-alkyloxy)methyl] derivates Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-10%

. Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- . 4.1 Description of first aid measures
- . General information: No special measures required.
- . After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stable in side position for transportation.

- . After skin contact: Immediately wash with water and soap and rinse thoroughly.
- . After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- . 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- . 5.1 Extinguishing media
- . Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- . 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- . 5.3 Advice for firefighters
- . Protective equipment: No special measures required.

GB-EN -

(Contd. on page 4)

www.bostik.it 3/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 3)

SECTION 6: Accidental release measures

. 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- . 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- . Information about fire and explosion protection: No special measures required.
- . 7.2 Conditions for safe storage, including any incompatibilities
- . Storage:
- . Requirements to be met by storerooms and receptacles: No special requirements.
- . Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep receptacle tightly sealed.
- . **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- . Additional information about design of technical facilities: No further data; see item 7.
- . 8.1 Control parameters
- . Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- . Additional information: The lists valid during the making were used as basis.
- . 8.2 Exposure controls
- Personal protective equipment:
- . General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

. Respiratory protection: Not required.

(Contd. on page 5)

GB-EN

www.bostik.it 4/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 4)

. Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

. For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

PVC or PE gloves

. Eye protection:



Tightly sealed goggles

. Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

. 9.1 Information on basic physical and chemical properties

. General Information

. Appearance:

Form: Fluid

Colour: According to product specification

. Odour: Characteristic
. Odour threshold: Not determined.

. **pH-value:** Not determined.

. Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 2,230 °C

. Flash point: 201 °C

. Flammability (solid, gas): Not applicable.

(Contd. on page 6)

- GB-EN

www.bostik.it 5/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

	(Contd. of page
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
Vapour pressure:	Not determined.
Density at 20 °C: Relative density Vapour density Evaporation rate	1.4 g/cm³ Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic at 20 °C: Kinematic: Organis solvents:	1 mPas Not determined. 0.0 %
9.2 Other information	All relevant physical data were determined for th

mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- . 10.1 Reactivity No further relevant information available.
- . 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- . 10.3 Possibility of hazardous reactions No dangerous reactions known.
- . 10.4 Conditions to avoid No further relevant information available.
- . 10.5 Incompatible materials: No further relevant information available.
- . 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- . 11.1 Information on toxicological effects
- . Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- . Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation. (Contd. on page 7)

www.bostik.it 6/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 6)

. Respiratory or skin sensitisation

May cause an allergic skin reaction.

- . CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- . Germ cell mutagenicity Based on available data, the classification criteria are not met.
- . Carcinogenicity Based on available data, the classification criteria are not met.
- . Reproductive toxicity Based on available data, the classification criteria are not met.
- . **STOT-single exposure** Based on available data, the classification criteria are not met.
- . **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- . Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- . 12.1 Toxicity
- . Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . 12.3 Bioaccumulative potential No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.
- . Ecotoxical effects:
- . Remark: Toxic for fish
- . Additional ecological information:
- . General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- . 12.5 Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . vPvB: Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- . 13.1 Waste treatment methods
- . Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- . Uncleaned packaging:
- . Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- . 14.1 UN-Number
- . ADR/ADN, IMDG, IATA UN3082

(Contd. on page 8)

GB-EN



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 7)

. 14.2 UN proper shipping name . ADR/ADN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A/F epoxy resins (number average molecular weight ≤700, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < = 700)) . IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A/F epoxy resins (number average molecular weight ≤700, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < = 700)), MARINE POLLUTANT . IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A/F epoxy resins (number average molecular weight ≤700, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < = 700))

. 14.3 Transport hazard class(es)

. ADR/ADN



. Class 9 (M6) Miscellaneous dangerous substances and articles.

. Label 9

. IMDG, IATA



. Class 9 Miscellaneous dangerous substances and

articles.

. Label

. 14.4 Packing group . ADR/ADN, IMDG, IATA

. ADR/ADN, IMDG, IATA III

. 14.5 Environmental hazards: Product contains environmentally hazardous

substances: bisphenol A/F epoxy resins (number

average molecular weight ≤700

. Marine pollutant: Yes

Symbol (fish and tree)

Special marking (ADR/ADN):

Symbol (fish and tree)

Special marking (IATA): Symbol (fish and tree)

(Contd. on page 9)

GB-EN

www.bostik.it 8/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

	(Contd. of page
14.6 Special precautions for user	Warning: Miscellaneous dangerous substance and articles.
Danger code (Kemler):	90
EMS Number:	F-A,S-F
Stowage Category	A
. 14.7 Transport in bulk according to An of Marpol and the IBC Code	nex II Not applicable.
Transport/Additional information:	
. ADR/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
- , ,	Maximum net quantity per inner packaging: 30 m
	Maximum net quantity per outer packaging: 100
	ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100 ml
Remarks:	Under certain conditions substances in Class
ivelliains.	(flammable liquids) can be classified
	packinggroup III.
	See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
	SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A
	EPOXY RESINS (NUMBER AVERAG
	MOLECULAR WEIGHT ≤700, REACTIO
	PRODUCT: BISPHENOL-A-(EPICHLORHYDRI
	EPOXY RESIN (NUMBER AVERAG
	MOLECULAR WEIGHT < = 700)), 9, III

SECTION 15: Regulatory information

- . 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Directive 2012/18/EU
- . Named dangerous substances ANNEX I None of the ingredients is listed.
- . **Seveso category** E2 Hazardous to the Aquatic Environment
- . Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- . REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

GB-EN

www.bostik.it 9/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 20 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 9)

. 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

- . Department issuing SDS: Bison QESH
- . Contact: Reach coördinator
- Abbreviations and acronyms:

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

. * Data compared to the previous version altered.

GB-EN

www.bostik.it 10/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 9 Revision: 16.08.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- . 1.1 Product identifier
- . Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT
- . **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- . Application of the substance / the mixture Adhesive
- . 1.3 Details of the supplier of the safety data sheet
- . Manufacturer(1)/Supplier(2):

1

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- . Further information obtainable from: Bison QESH
- . **1.4 Emergency telephone number:** +31 88 3235700

SECTION 2: Hazards identification

- . 2.1 Classification of the substance or mixture
- . Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- 2.2 Label elements
- . Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

. Hazard pictograms





GHS05 GHS07

- . Signal word Danger
- . Hazard-determining components of labelling:

Amines, polyethylenepoly-, triethylenetetramine fraction 2,4,6-tris(dimethylaminomethyl)phenol

(Contd. on page 2)

GB-EN

www.bostik.it 11/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 9 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 1)

. Hazard statements

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

. Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with national regulations.

. 2.3 Other hazards

- . Results of PBT and vPvB assessment
- . **PBT:** Not applicable. . **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- . 3.2 Mixtures
- . Description: Adhesive

. Dangerous components:			
CAS: 100-51-6 EINECS: 202-859-9	♠ Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2,	2.5-10%	
EINECS: 292-588-2	H319 Amines, polyethylenepoly-, triethylenetetramine fraction Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox.	2.5-10%	
CAS: 90-72-2 EINECS: 202-013-9	4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4	2.5-10%	
	H302; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	,	

. Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- . 4.1 Description of first aid measures
- . General information: No special measures required.
- . After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stable in side position for transportation.

Call a doctor immediately.

- . After skin contact: Immediately wash with water and soap and rinse thoroughly.
- . After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

(Contd. on page 3)

GB-EN



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 9 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 2)

. 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- . 5.1 Extinguishing media
- . Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- . 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- . 5.3 Advice for firefighters
- . Protective equipment: No special measures required.

SECTION 6: Accidental release measures

. 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- . **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- . **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- . Information about fire and explosion protection: No special measures required.
- . 7.2 Conditions for safe storage, including any incompatibilities
- . Storage:
- . Requirements to be met by storerooms and receptacles: No special requirements.
- . Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep receptacle tightly sealed.
- . **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- . Additional information about design of technical facilities: No further data; see item 7.
- . 8.1 Control parameters
- . Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

GB-EN

www.bostik.it 13/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 9 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 3)

- . Additional information: The lists valid during the making were used as basis.
- . 8.2 Exposure controls
- . Personal protective equipment:
- . General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- . Respiratory protection: Not required.
- Protection of hands:



Protective gloves

PVC or PE gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Not required.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

. For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

PVC or PE gloves

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

PVC or PE gloves

Neoprene gloves

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

PVC or PE gloves

. As protection from splashes gloves made of the following materials are suitable:

PVC or PE gloves

(Contd. on page 5)

GB-EN

www.bostik.it 14/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 9 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 4)

. Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

. 9.1 Information on basic physical and chemical properties

. General Information

. Appearance:

Form: Fluid
Colour: Light yellow
. Odour: Amine-like
. Odour threshold: Not determined.
. pH-value: Not determined.

. Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 205 °C

. Flash point: 101 °C

. Flammability (solid, gas): Not applicable.

. Ignition temperature: 435 °C

. **Decomposition temperature:** Not determined.

. **Auto-ignition temperature:** Product is not selfigniting.

. **Explosive properties:** Product does not present an explosion hazard.

. Explosion limits:

Lower: Not determined. **Upper:** Not determined.

. Vapour pressure: Not determined.

Density: Not determined.
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not determined.

. Solubility in / Miscibility with

water: Not miscible or difficult to mix.

. Partition coefficient: n-octanol/water: Not determined.

. Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Organis solvents: 0.0 %

(Contd. on page 6)

GB-EN

www.bostik.it 15/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 9 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 5)

. **9.2 Other information**All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- . 10.1 Reactivity No further relevant information available.
- . 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- . 10.3 Possibility of hazardous reactions Corrosive action on metals.
- . 10.4 Conditions to avoid No further relevant information available.
- . 10.5 Incompatible materials: No further relevant information available.
- . 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- . 11.1 Information on toxicological effects
- . Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

100-51-6 Benzyl alcohol

Oral LD50 1230 mg/kg (rat)
Dermal LD50 2000 mg/kg (rbt)

- . Primary irritant effect:
- . Skin corrosion/irritation Based on available data, the classification criteria are not met.
- . Serious eye damage/irritation

Causes serious eye damage.

. Respiratory or skin sensitisation

May cause an allergic skin reaction.

- . CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- . Germ cell mutagenicity Based on available data, the classification criteria are not met.
- . Carcinogenicity Based on available data, the classification criteria are not met.
- . Reproductive toxicity Based on available data, the classification criteria are not met.
- . STOT-single exposure Based on available data, the classification criteria are not met.
- . STOT-repeated exposure Based on available data, the classification criteria are not met.
- . Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- . 12.1 Toxicity
- . Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . 12.3 Bioaccumulative potential No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

GB-EN



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 9 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 6)

(Contd. on page 8)

GB-EN

. Additional ecological information:

. General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- . 12.5 Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . vPvB: Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- . 13.1 Waste treatment methods
- . Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information		
14.1 UN-Number ADR/ADN, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR/ADN, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR/ADN, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR/ADN, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Anr of Marpol and the IBC Code	nex II Not applicable.	
Transport/Additional information:		
. IMDG . Remarks:	Under certain conditions substances in Class (flammable liquids) can be classified packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.	

www.bostik.it 17/18



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.09.2017 Version number 9 Revision: 16.08.2017

Trade name: BOSTIK MATERIALI EDILI FPB 2X65ML A1*6 IT

(Contd. of page 7)

. UN "Model Regulation":

Void

SECTION 15: Regulatory information

- . 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Directive 2012/18/EU
- . Named dangerous substances ANNEX I None of the ingredients is listed.
- . REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- . 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

- . Department issuing SDS: Bison QESH
- . Contact: Reach coördinator

. Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

. * Data compared to the previous version altered.

GB-EN

www.bostik.it 18/18