

Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

. 1.1 Product identifier

. Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

- . **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- . Application of the substance / the mixture Cleaning agent/ Cleaner

. 1.3 Details of the supplier of the safety data sheet

. Manufacturer(1)/Supplier(2):

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com


. Further information obtainable from: Bison QESH

. 1.4 Emergency telephone number: +31 88 3235700

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame



GHS07

Eye Irrit. 2 H319	Causes serious eye irritation.
STOT SE 3 H336	May cause drowsiness or dizziness.

. 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. **Hazard pictograms**



. Signal word Danger

(Contd. on page 2)



Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

	(Contd. of page
Hazard-c	letermining components of labelling:
acetone	
Hazard s	tatements
H222-H2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
Precauti	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition source No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P410+P4	12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with national regulations.
Addition	al information:
EUH066	Repeated exposure may cause skin dryness or cracking.
	r hazards
Results	of PBT and vPvB assessment
	applicable.

SECTION 3: Composition/information on ingredients

- . 3.2 Mixtures
- . Description: Cleansing product

. Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone	50-100%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane � Flam. Gas 1, H220; Press. Gas C, H280	2.5-10%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ♦ Press. Gas L, H280	2.5-10%
CAS: 74-98-6 EINECS: 200-827-9	propane 🚸 Flam. Gas 1, H220; Press. Gas C, H280	1.0-2.5%
. Additional information:		

Propellant: CO2

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

. 4.1 Description of first aid measures

- . General information: No special measures required.
- . After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

GB-EN



Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

(Contd. of page 2)

Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

. After skin contact: Generally the product does not irritate the skin.

. After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. **After swallowing:** Do not induce vomiting; call for medical help immediately.

- . 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

. 5.1 Extinguishing media

. Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.

. 5.3 Advice for firefighters

. Protective equipment: No special measures required.

SECTION 6: Accidental release measures

. 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

. 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

. Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

. 7.2 Conditions for safe storage, including any incompatibilities

. Storage:

. Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Not required.

. Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

GB-EN



Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

(Contd. of page 3)

Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

. 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

. Additional information about design of technical facilities: No further data; see item 7.

. 8.1 Control parameters

. Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone	
WEL (Great Britain)	Short tor

WEL (Great Britain)Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppmIOELV (European Union)Long-term value: 1210 mg/m³, 500 ppm

124-38-9 carbon dioxide

WEL (Great Britain) Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm

IOELV (European Union) Long-term value: 9000 mg/m³, 5000 ppm

. Additional information: The lists valid during the making were used as basis.

. 8.2 Exposure controls

- . Personal protective equipment:
- . General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

. Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

. Recommended filter device for short term use: Filter AX

. Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

. For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

PVC or PE gloves

(Contd. on page 5)



Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

(Contd. of page 4)

Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

. Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemi		
 9.1 Information on basic physical and General Information Appearance: 	chemical properties	
Form:	Aerosol	
Colour:	According to product specification	
. Odour: . Odour threshold:	Characteristic Not determined.	
. pH-value:	Not determined.	
•	Not determined.	
. Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : -44 °C	
. Flash point:	-97 °C	
. Flammability (solid, gas):	Not applicable.	
. Ignition temperature:	460 °C	
. Decomposition temperature:	Not determined.	
. Auto-ignition temperature:	Product is not selfigniting.	
. Explosive properties:	Not determined.	
. Explosion limits: Lower: Upper:	2.6 Vol % 13.0 Vol %	
Vapour pressure at 20 °C:	233 hPa	
Density at 20 °C: Relative density Vapour density Evaporation rate	0.895 g/cm ³ Not determined. Not determined. Not applicable.	
. Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
. Partition coefficient: n-octanol/water:	Not determined.	
. Viscosity: Dynamic: Kinematic: Organis solvents:	Not determined. Not determined. 82.0 %	

GB-EN



Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

(Contd. of page 5)

Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

. 9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- . **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- . 10.3 Possibility of hazardous reactions No dangerous reactions known.
- . 10.4 Conditions to avoid No further relevant information available.
- . 10.5 Incompatible materials: No further relevant information available.
- . 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- . 11.1 Information on toxicological effects
- . Acute toxicity Based on available data, the classification criteria are not met.

. LD/LC50 values relevant for classification:

67-64-1 acetone

 Oral
 LD50
 5800 mg/kg (rat)

 Dermal
 LD50
 20000 mg/kg (rbt)

. Primary irritant effect:

- . Skin corrosion/irritation Based on available data, the classification criteria are not met.
- . Serious eye damage/irritation
- Causes serious eye irritation.
- . Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- . Germ cell mutagenicity Based on available data, the classification criteria are not met.
- . Carcinogenicity Based on available data, the classification criteria are not met.
- . Reproductive toxicity Based on available data, the classification criteria are not met.
- . STOT-single exposure
- May cause drowsiness or dizziness.
- . STOT-repeated exposure Based on available data, the classification criteria are not met.
- . Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- . 12.1 Toxicity
- . Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . 12.3 Bioaccumulative potential No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)



Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

(Contd. of page 6)

Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

. Additional ecological information:

. General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- . 12.5 Results of PBT and vPvB assessment
- . **PBT:** Not applicable.
- . vPvB: Not applicable.

. 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

. 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- . Uncleaned packaging:
- . Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN-Number ADR/ADN, IMDG, IATA	UN1950	
14.2 UN proper shipping name ADR/ADN IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR/ADN		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
Class	2.1	
Label	2.1	



Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

	(Contd. of page
14.4 Packing group ADR/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacit of 1 litre: Category A. For AEROSOLS with capacity above 1 litre: Category B. For WAST AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacit of 1 litre: Segregation as for class 9. Stor "separated from" class 1 except for division 1.4 For AEROSOLS with a capacity above 1 litre Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation a for the appropriate subdivision of class 2.
14.7 Transport in bulk according to An of Marpol and the IBC Code	inex II
•	Not applicable.
Transport/Additional information: ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category	1L Code: E0 Not permitted as Excepted Quantity 2
Transport/Additional information: ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity 2 D 1L Code: E0
Transport/Additional information: ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	1L Code: E0 Not permitted as Excepted Quantity 2 D

SECTION 15: Regulatory information

. 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

. Named dangerous substances - ANNEX I None of the ingredients is listed.

. Seveso category P3a FLAMMABLE AEROSOLS

(Contd. on page 9) GB-EN



Printing date 13.08.2017

Version number 14

Revision: 13.08.2017

Trade name: BOSTIK PU CLEANER AER 500ML*12 IT

(Contd. of page 8)

- . Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- . Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- . REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

. 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- . Department issuing SDS: Bison QESH
- Contact: Marketing UHU BOSTIK Reach coördinator

. **Abbreviations and acronyms:** Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas C: Gases under pressure – Compressed gas Press. Gas L: Gases under pressure – Liquefied gas Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB-EN -