

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2017 Version number 19 Revision: 16.08.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- . 1.1 Product identifier
- . Trade name: BOSTIK LEGNO POLIURETANICA BOT 750G*6 IT
- . CAS Number:

9016-87-9

. EC number:

202-966-0

. Index number:

615-005-01-6

- . 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- . Application of the substance / the mixture Adhesive
- . 1.3 Details of the supplier of the safety data sheet
- . Manufacturer(1)/Supplier(2):

1

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- . Further information obtainable from: Bison QESH
- . 1.4 Emergency telephone number: +31 88 3235700

SECTION 2: Hazards identification

- . 2.1 Classification of the substance or mixture
- . Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

GB-EN

www.bostik.it 1/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2017 Version number 19 Revision: 16.08.2017

Trade name: BOSTIK LEGNO POLIURETANICA BOT 750G*6 IT

(Contd. of page 1)

- . 2.2 Label elements
- . Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

. Hazard pictograms





GHS07 GHS08

- . Signal word Danger
- . Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues

- . Hazard statements
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

. Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P260 Do not breathe vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

==>> Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms





GHS07 GHS08

- . Signal word Danger
- . Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomeres and homologues

Hazard statements

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 3)

GR-FN

www.bostik.it 2/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2017 Version number 19 Revision: 16.08.2017

Trade name: BOSTIK LEGNO POLIURETANICA BOT 750G*6 IT

(Contd. of page 2)

. Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P260 Do not breathe vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

. 2.3 Other hazards

. Results of PBT and vPvB assessment

. **PBT:** Not applicable. . **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

. 3.1 Substances

. CAS No. Description

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

. Identification number(s) . EC number: 202-966-0 . Index number: 615-005-01-6

. Dangerous components: Void

SECTION 4: First aid measures

. 4.1 Description of first aid measures

. General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stable in side position for transportation.

- . After skin contact: Immediately wash with water and soap and rinse thoroughly.
- . After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- . 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- . 5.1 Extinguishing media
- . Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- . 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

GB-EN

www.bostik.it 3/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2017 Version number 19 Revision: 16.08.2017

Trade name: BOSTIK LEGNO POLIURETANICA BOT 750G*6 IT

(Contd. of page 3)

. 5.3 Advice for firefighters

. **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

. **6.2 Environmental precautions:** No special measures required.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

. 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- . Information about fire and explosion protection: Keep respiratory protective device available.
- . 7.2 Conditions for safe storage, including any incompatibilities
- . Storage:
- . Requirements to be met by storerooms and receptacles: No special requirements.
- . Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep receptacle tightly sealed.
- . **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- . Additional information about design of technical facilities: No further data; see item 7.
- . 8.1 Control parameters
- . Ingredients with limit values that require monitoring at the workplace: Not required.
- . Additional information: The lists valid during the making were used as basis.
- . 8.2 Exposure controls
- Personal protective equipment:
- . General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

(Contd. on page 5)

GB-EN

www.bostik.it 4/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2017 Version number 19 Revision: 16.08.2017

Trade name: BOSTIK LEGNO POLIURETANICA BOT 750G*6 IT

(Contd. of page 4)

- . Respiratory protection: Not required.
- . Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

. For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

PVC or PE gloves

Eye protection:



Tightly sealed goggles

. Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

. 9.1 Information on basic physical and chemical properties

. General Information

. Appearance:

Form: Liquid

Colour: According to product specification

. **Odour:** Characteristic . **Odour threshold:** Not determined.

. **pH-value:** Not determined.

. Change in condition

Melting point/freezing point: <0 °C Initial boiling point and boiling range: 190 °C

. Flash point: >110 °C

. Flammability (solid, gas): Not applicable.

. Ignition temperature: 400 °C

. **Decomposition temperature:** Not determined.

(Contd. on page 6)

- GB-EN -

www.bostik.it 5/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2017 Version number 19 Revision: 16.08.2017

Trade name: BOSTIK LEGNO POLIURETANICA BOT 750G*6 IT

	(Contd. of page
Auto-ignition temperature:	Not determined.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure at 25 °C:	0.0002 hPa
Density at 20 °C:	1.13 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organis solvents:	0.0 %
9.2 Other information	All relevant physical data were determined for th mixture. All non-determined data are not measurable on the relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- . 10.1 Reactivity No further relevant information available.
- . 10.2 Chemical stability
- . Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- . **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- . 10.4 Conditions to avoid No further relevant information available.
- . **10.5 Incompatible materials:** No further relevant information available.
- . 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- . 11.1 Information on toxicological effects
- . Acute toxicity

Harmful if inhaled.

- . Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

. Serious eye damage/irritation

Causes serious eye irritation.

. Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 7)

GB-EN

www.bostik.it 6/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2017 Version number 19 Revision: 16.08.2017

Trade name: BOSTIK LEGNO POLIURETANICA BOT 750G*6 IT

(Contd. of page 6)

May cause an allergic skin reaction.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- . Germ cell mutagenicity Based on available data, the classification criteria are not met.
- . Carcinogenicity

Suspected of causing cancer.

- . Reproductive toxicity Based on available data, the classification criteria are not met.
- . STOT-single exposure
- May cause respiratory irritation.
- . STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- . Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- . 12.1 Toxicity
- . Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . 12.3 Bioaccumulative potential No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- . General notes: Generally not hazardous for water
- . 12.5 Results of PBT and vPvB assessment
- . **PBT:** Not applicable.
- . vPvB: Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- . 13.1 Waste treatment methods
- . Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

. 14.1 UN-Number

. ADR/ADN, ADN, IMDG, IATA Void

. 14.2 UN proper shipping name

. ADR/ADN, ADN, IMDG, IATA Void

(Contd. on page 8)

GB-EN

www.bostik.it 7/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2017 Version number 19 Revision: 16.08.2017

Trade name: BOSTIK LEGNO POLIURETANICA BOT 750G*6 IT

(Contd. of page 7
Void
Void
No
Not applicable.
nnex II Not applicable.
Under certain conditions substances in Class 3 (flammable liquids) can be classified ir packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
Void

SECTION 15: Regulatory information

- . 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Directive 2012/18/EU
- Named dangerous substances ANNEX I Substance is not listed.
- . REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- . 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- . Department issuing SDS: Bison QESH
- Contact: Reach coördinator
- Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.

GB-EN

8/8 www.bostik.it