

Printing date 14.08.2017

Version number 19

Revision: 14.08.2017

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

. 1.1 Product identifier

. Trade name: BOSTIK LEGNO PU FIBRA TIXOTROPICO CRT 325G*12 IT

. **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

. Application of the substance / the mixture Adhesive

. 1.3 Details of the supplier of the safety data sheet

. Manufacturer(1)/Supplier(2):

Bison International Dr.A.F.Philipsstraat 9 NL-4462 EW Goes PO Box 160 NL-4460 AD Goes tel. +31 88 3235700 fax. +31 88 3235800 e mail: sds@boltonadhesives.com

. Further information obtainable from: Bison QESH

. 1.4 Emergency telephone number: +31 88 3235700

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS08 health hazard Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. Carc. 2 H351 Suspected of causing cancer. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)




Printing date 14.08.2017

Version number 19

Revision: 14.08.2017

Trade name: BOSTIK LEGNO PU FIBRA TIXOTROPICO CRT 325G*12 IT



3.2 Mixtures Description: Adhesive			
. Dangerous components:			
	Isocyanates, reaction product of polyol with methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	50-100%	
CAS: 26447-40-5 EINECS: 247-714-0	methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ① Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-50%	



Printing date 14.08.2017

Version number 19

Revision: 14.08.2017

Trade name: BOSTIK LEGNO PU FIBRA TIXOTROPICO CRT 325G*12 IT

. Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

. 4.1 Description of first aid measures

. General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

. After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stable in side position for transportation.

- . After skin contact: Immediately wash with water and soap and rinse thoroughly.
- . After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

. After swallowing: Do not induce vomiting; call for medical help immediately.

- . **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- . 5.1 Extinguishing media
- . Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- . 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- . 5.3 Advice for firefighters
- . Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

. 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

. 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB-EN



Printing date 14.08.2017

Version number 19

Revision: 14.08.2017

(Contd. of page 3)

Trade name: BOSTIK LEGNO PU FIBRA TIXOTROPICO CRT 325G*12 IT

See Section 13 for disposal information.

SECTION 7: Handling and storage

. 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

. Information about fire - and explosion protection: Keep respiratory protective device available.

. 7.2 Conditions for safe storage, including any incompatibilities

. Storage:

. Requirements to be met by storerooms and receptacles: No special requirements.

. Information about storage in one common storage facility: Not required.

. Further information about storage conditions: Keep receptacle tightly sealed.

. 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

. Additional information about design of technical facilities: No further data; see item 7.

- . 8.1 Control parameters
- . Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- . Additional information: The lists valid during the making were used as basis.
- . 8.2 Exposure controls
- . Personal protective equipment:
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- . Respiratory protection: Not required.
- . Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several (Contd. on page 5)

- GB-EN



Printing date 14.08.2017

Version number 19

Revision: 14.08.2017

Trade name: BOSTIK LEGNO PU FIBRA TIXOTROPICO CRT 325G*12 IT

(Contd. of page 4)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- . For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- PVC or PE gloves

. Eye protection:



Tightly sealed goggles

. Body protection: Use protective suit.

9.1 Information on basic physical and chemical properties		
General Information		
. Appearance:		
Form:	Fluid	
Colour:	According to product specification	
. Odour: . Odour threshold:	Characteristic Not determined.	
. Odour threshold:	Not determined.	
. pH-value:	Not determined.	
. Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	190 °C	
. Flash point:	111 °C	
. Flammability (solid, gas):	Not applicable.	
. Ignition temperature:	400 °C	
. Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
. Explosive properties:	Product does not present an explosion hazard.	
. Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
. Vapour pressure:	Not determined.	
. Density:	Not determined.	
. Relative density	Not determined.	
. Vapour density	Not determined.	
. Evaporation rate	Not determined.	



Printing date 14.08.2017

Version number 19

Revision: 14.08.2017

Trade name: BOSTIK LEGNO PU FIBRA TIXOTROPICO CRT 325G*12 IT

	(Contd. of page 5)	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
. Partition coefficient: n-octanol/water:	Not determined.	
. Viscosity: Dynamic at 20 °C: Kinematic: Organis solvents: . 9.2 Other information	150000 mPas Not determined. 0.0 % All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.	

SECTION 10: Stability and reactivity

. 10.1 Reactivity No further relevant information available.

- . 10.2 Chemical stability
- . Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions

Reacts with alcohols. Reacts with water.

Reacts with alkali, amines and strong acids.

- . **10.4 Conditions to avoid** No further relevant information available.
- . 10.5 Incompatible materials: No further relevant information available.
- . 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

SECTION 11: Toxicological information

- . 11.1 Information on toxicological effects
- Acute toxicity
- Harmful if inhaled.
- . Primary irritant effect:
- . Skin corrosion/irritation
- Causes skin irritation.
- . Serious eye damage/irritation
- Causes serious eye irritation.
- . Respiratory or skin sensitisation
- May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
- . CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- . Germ cell mutagenicity Based on available data, the classification criteria are not met.
- . Carcinogenicity
- Suspected of causing cancer.
- . Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause respiratory irritation.
- . STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 7)

GB-EN



Printing date 14.08.2017

Version number 19

Revision: 14.08.2017

(Contd. of page 6)

Trade name: BOSTIK LEGNO PU FIBRA TIXOTROPICO CRT 325G*12 IT

. Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- . 12.1 Toxicity
- . Aquatic toxicity: No further relevant information available.
- . 12.2 Persistence and degradability No further relevant information available.
- . **12.3 Bioaccumulative potential** No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.
- . Additional ecological information:

. General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- . 12.5 Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . **vPvB:** Not applicable.

. 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

. 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

. Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

. 14.1 UN-Number . ADR/ADN, ADN, IMDG, IATA	Void	
. 14.2 UN proper shipping name . ADR/ADN, ADN, IMDG, IATA	Void	
. 14.3 Transport hazard class(es)		
. ADR/ADN, ADN, IMDG, IATA		
. Class	Void	
. 14.4 Packing group		
ADR/ADN, IMDG, IATA	Void	
. 14.5 Environmental hazards:		
. Marine pollutant:	No	



Printing date 14.08.2017

Version number 19

Revision: 14.08.2017

Trade name: BOSTIK LEGNO PU FIBRA TIXOTROPICO CRT 325G*12 IT

	(Contd. of page 7
. 14.6 Special precautions for user	Not applicable.
. 14.7 Transport in bulk according to Annex I of Marpol and the IBC Code	Not applicable.
. Transport/Additional information:	
. IMDG . Remarks:	Under certain conditions substances in Class 3 (flammable liquids) can be classified in packinggroup III. See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
. UN "Model Regulation":	Void

SECTION 15: Regulatory information

- . 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Directive 2012/18/EU
- . Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- . Department issuing SDS: Bison QESH
- Contact: Reach coördinator

. Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

GB-EN -