



# GOMMA LIQUIDA ACCELERATORE

## ACCELERATES RUBBER SEAL® TOP LAYER DRYING PROCESS



### TECHNICAL SPECIFICATIONS

Colour after curing/drying:	Transparent
Density approx.:	1,0 g/cm <sup>3</sup>
Minimum application temperature:	5 °C
Maximum application temperature:	35 °C
pH-value approx.:	7

### PACK SIZES

1 liter Trigger Bottle

### STORAGE CONDITIONS

A minimum of 3 years.

Properly sealed packages should be stored in a dry, cool, frost-proof, ventilated location at temperatures between +5°C and +25°C.

### PRODUCT DESCRIPTION

Spray that accelerates the Rubber Seal® top layer drying process and is water proof after 10 minutes. Ideal in turbulent weather conditions.

### FIELD OF APPLICATION

To use on Rubber Seal® Liquid Rubber.

### PROPERTIES

Accelerator does not affect the technical properties of Rubber Seal® Liquid Rubber.

### PREPARATION

**Working Conditions:** Use at temperatures between +5°C and +35°C.

**Personal safety:** Wear eye protection and wash hands thoroughly after handling.

### APPLICATION

#### Directions for use:

Spray Accelerator on the Rubber Seal® coating. Rubber Seal® is dry-to-touch 2 minutes after using Accelerator, can withstand light rain after 5 minutes, and is completely impervious to rainfall and water after 10 minutes. Make sure that Rubber Seal® is completely dry before applying a new Rubber Seal® layer. Use water to clean tools afterwards.

**Points of attention:** Risk of corrosion: there is a risk of corrosion on untreated steel and iron. Use on non-porous surfaces: when using Rubber Seal® in combination with Accelerator, we recommend applying several thin layers (of approx. 1.0 mm) of Rubber Seal® coating. When applying thicker layers, the final curing of the coating in combination with Rubber Seal® Accelerator can be delayed.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.