



MALTALASTIC

READY TO USE, SYNTHETIC FILLER



PRODUCT DESCRIPTION

Ready to use synthetic filler Ideal for fast and easy filling of non-moving cracks, crevices and holes in walls, ceilings, (parquet) floors, stairs and wood. White colour.

FIELD OF APPLICATION

Suitable for fast and easy filling of non-moving cracks, crevices and holes in walls, ceilings, (parquet) floors, stairs, window frames and wood. Universal; Excellent adhesion on many surfaces.

Not suitable for places with permanent high humidity and/or prolonged contact with water. Not suitable for polyethylene (PE), polypropylene (PP) and PTFE

PROPERTIES

- Quick-drying
- No or hardly any shrinkage
- Somewhat elastic
- Easy to sand
- Well-smoothed finish
- Paintable
- Nailing and screwing possible
- Ready to use
- Solvent-free

PREPARATION

Working Conditions: Only apply at temperatures between +5°C and +40°C.

Surface Requirements: The surface must be dry, clean and free of dust, rust and grease.

Preliminary Surface Treatment: Painting (insulating) nails and other metal parts in the substrate to prevent corrosion, which may avoid staining.

Tools: Putty knife. Clean tools immediately after use with warm water.

APPLICATION

Directions for use:

Stir product before use.

Apply product straight from the tube and press it firmly into the damage with a putty knife. Ensure a good adhesion to the substrate and the walls of the damage. Following this smooth finish immediately with a wet putty knife. Work in layers of up to 5 mm thick. If necessary, work in multiple layers. A next layer should be applied only after the previous one is completely dry. After drying, sand or paint if necessary (all kinds of wall paint).

Stains/residue: Remove stains immediately with a wet cloth.

Cured stains can only be removed mechanically.

Advice: For outdoor applications, always paint.

Points of attention: Ensure the joint remains dry for at least the first 8 hours. The product is limited loadable; do not subject to excessive weight or forces.

TECHNICAL SPECIFICATIONS

Colour:	White
Density approx.:	1,45 g/cm ³
Elasticity:	Limited
Moisture resistance:	Good
Viscosity:	Pasty

STORAGE CONDITIONS

Store in properly sealed packaging in a dry place at between +5°C and +25°C.