



DOUBLEFIX REMOVABLE INDOORS 1,5M ROLL

EXTRA-STRONG, REMOVABLE DOUBLE-SIDED MOUNTING TAPE



PRODUCT DESCRIPTION

Extra-strong double-sided tape for mounting and affixing objects in indoor areas. The simple alternative to screws and nails. Can be removed without leaving traces. Provides a secure hold on almost all smooth surfaces, e.g. metal, tiles, plastic, glass and painted wood. Ideal for mounting mirrors, holders, signs, hooks, shelving elements, cable channels, decorative objects, decorative profiles, and much more. Fully load-bearing after 60 minutes. Moisture-resistant.

FIELD OF APPLICATION

For quick, clean and easy mounting and fixing of objects like mirrors, soap dishes, suspension hooks, name plates, plastic holders, etc. on smooth and even surfaces indoors. Suitable for metal, tiles, plastic, glass, painted wood, etc. Ideal for use in sanitary rooms and kitchens.

Not suitable for application on rough surfaces (stone, decorative plaster) and vinyl wall covering.

PROPERTIES

- double-sided mounting tape
- extra-strong
- removable
- for smooth surfaces
- for indoor areas
- humidity resistant
- temperature resistant
- clean, easy, fast

PREPARATION

Working Conditions: The minimum working temperature is 10°C.

Surface Requirements: The surface must be clean, dry, free of dust and grease.

Preliminary Surface Treatment: For best results, first cleanse the surfaces to be glued (e.g. with alcohol or white spirit).

APPLICATION

Coverage: 2 cm per 350 g

Directions for use:

First mark all the corners of the object on the backside, because once objects are fixed it is practically impossible to move them without damaging the adhesive strips. Apply sufficient tape to the back of the object to mount (2 cm per 350 g). Remove the protective foil. Place the object in the right spot and press firmly. Removal: simply pull off the tape from the substrate. Leaves no residue.

Points of attention: Do not touch the adhesive as this reduces the tape's adhesive strength.

TECHNICAL SPECIFICATIONS

Carrier type:	Polyester fabric
Chemical base:	Synthetic rubber
Chemicals resistance:	Limited
Colour:	White
Holding power:	>168 (1kg)
Initial tack:	High
Minimum temperature resistance:	-10 °C
Maximum temperature resistance:	75 °C
Moisture resistance:	Good
Peel adhesion:	SS 30 N/25mm
Rolling ball tack:	1 cm
Tensile Strength (N/25 mm) approx.:	65 N/25 mm
Thickness (mm):	0.27 mm
UV resistance:	Good

STORAGE CONDITIONS

Store in a dry, cool and frost free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.