



# LUBRIT-ALL®

## MULTIFUNCTIONAL MAINTENANCE AGENT



### APPLICATION

#### Directions for use:

Shake well before use. Spray surface(s) evenly from a distance of approx. 10-20 cm. For use as penetrating oil, spray surface(s) generously. After about 5 -10 minutes, the parts can be disassembled. For preventive use parts must be treated first, then assembled.

**Stains/residue:** Remove stains with Griffon Primor or degreaser.

**Points of attention:** Use the additional spray hose integrated in the cap for optimum dosage.

### TECHNICAL PROPERTIES

**Temperature resistance:** -50°C - +125°C

### TECHNICAL SPECIFICATIONS

**Chemical base:** Solvents and mineral oil

**Colour:** Transparent

### STORAGE CONDITIONS

A minimum of 36 months. Close the container properly and store in a dry, cool and frost-free location.

### PRODUCT DESCRIPTION

Multifunctional maintenance agent for lubricating, protecting, cleaning and loosening in 1001 applications.

### FIELD OF APPLICATION

For lubricating, protecting, cleaning and loosening in 1001 applications, such as in the home, workshop, garage, garden, caravan, car and boat. Suitable for, e.g., lubricating sliding doors, windows, hinges, latches, locks and roller bearings.

Also for maintenance of (motor) bikes, scooters, machinery, (garden) tools and sports equipment. Also for removing dirt and grease from wheel rims, (bicycle) chains, gears, bearings and loosening rusted and oxidised (fixation) materials such as bolts and nuts.

### PROPERTIES

- Lubricates
- Protects
- Removes dirt and grease
- Unlatches
- Corrosion retardant
- Dissolves dirt and oxides
- Moisture repellent
- Silicone-free
- With extra precision spray hose
- Can be used in all positions

### PREPARATION

**Preliminary surface treatment:** Make sure that the surface is clean, dry, and free of grease.