



GAS LEAK FINDER

FOR DETECTING LEAKS IN GAS AND COMPRESSED AIR PIPING



TECHNICAL SPECIFICATIONS

Chemical base: Acid-free soap solution

Colour: White (Transparent)

STORAGE CONDITIONS

At least 36 months after production. Close the container properly and store in a dry, cool and frost-free location.

PRODUCT DESCRIPTION

For detecting leaks in gas and compressed air piping.

FIELD OF APPLICATION

For the detection of leaks, e.g., in piping, fittings, valves and taps in gas and compressed air systems, refrigeration and airconditioning systems, pressure vessels, tanks, furnaces, burners, gas cylinders and compressors. Suitable for all (combustible) types of gases (including oxygen and freon).

PROPERTIES

- Non-corrosive
- Non-flammable
- Non-toxic
- Can be used in all positions

QUALITY LABELS/STANDARDS

Certificates: Gastec QA: Foaming Gas Leak Detector based on GASTEC QA demands 120.

PREPARATION

Working conditions: Do not apply at temperatures below 0°C.

APPLICATION

Directions for use:

Shake well before use. Pressurise the system to check and inject from a distance of about 30-50 cm. In case of leaks, bubbles will develop. For very small leaks this may take some time.

Stains/residue: Remove stains with water.