



PTFE-TAPE DIN-EN

PTFE TAPE FOR SEALING METAL AND SYNTHETIC THREADED CONNECTIONS.



TECHNICAL SPECIFICATIONS

Chemical base: PTFE

Colour: White

STORAGE CONDITIONS

A minimum of 24 months. Store in properly sealed packaging in a dry place at between +5°C and +25°C.

PRODUCT DESCRIPTION

PTFE tape for sealing metal and synthetic threaded connections.

FIELD OF APPLICATION

For sealing metal and synthetic threaded connections. Suitable for gas, water, oxygen, steam, fuels, solvents and acids. For gas: Maximum operating pressure 0.2 bar at an ambient temperature of -20°C to 135°C. Not suitable for gas (Netherlands).

PROPERTIES

- 100% PTFE
- Chemical resistant
- Mould resistant
- UV resistant
- Removable
- Immediately loadable

QUALITY LABELS/STANDARDS

Standards: EN 751-3: Sealing materials for metallic threaded joints in contact with 1st, 2nd and 3rd family gasses and hot water. Part 3 Unsintered PTFE Tapes.

PREPARATION

Preliminary surface treatment: Thoroughly clean and degrease surfaces.

TECHNICAL PROPERTIES

Water resistance: Very good

Temperature resistance: -200°C to +260°C.

Chemicals resistance: Very good.