

SUPER CUTTER

MULTIPURPOSE TOOL



(3) Removing cured sealant

Insert the hook-shaped portion of the Super Cutter in the cured sealant and loosen the sealant. Use the pointed part on places which are hard to reach (such as in corners).

Points of attention: Always follow the manufacturer's instructions regarding the sealant.

TECHNICAL SPECIFICATIONS

Colour: Blue

Viscosity: approx. 0 mPa.s.

PRODUCT DESCRIPTION

Convenient and multi-functional tool for smoothing joints and for removing existing joints and sealant residues. Also for opening the cartridge and cutting the nozzle.

FIELD OF APPLICATION

Suitable for use with all sealants such as Silicone Sealant, Acrylic Sealant or Poly Max®.

PREPARATION

Personal safety: The Super Cutter is equipped with a sharp knife. Avoid contact with fingers, etc.

APPLICATION

Directions for use:

(1) Cut open cartridge / cut off nozzle

Opening the cartridge: Place the Super Cutter straight on the cartridge closure (plastic threaded nipple). Cut off the cartridge closure straight using the built-in cutter.

Cutting the Nozzle: With the built-in cutter cut off the nozzle at the desired diameter diagonally.

(2) Finishing / remove excess sealant

After the sealant is applied, moisten the sealant with soap water. Moisten the spoon-shaped side of the Super Cutter also with soapy water. Place it then against the sealant and tool off the excess sealant in one smooth movement. Collect excess sealant in the spoon. Place the Super Cutter perpendicular to the sealant joint for narrow joints. For a wider joint, hold the Super Cutter flatter. Smoothen any uneven parts with a wet finger.