



# RIPARA LEGNO

## IRONCLAD DUAL-COMPONENT EPOXY PUTTY FOR WOOD.



mixing and put into shape. Cut off excess mass with a knife. Remove fingerprints by rubbing with water or a damp cloth before curing starts.

**Stains/residue:** Remove fingerprints by rubbing with water or a damp cloth before curing starts.

### TECHNICAL PROPERTIES

**Moisture resistance:** Very good

**UV resistance:** Good

**Filling capacity:** Very good

### TECHNICAL SPECIFICATIONS

**Colour:** Light brown

**Viscosity:** approx. 0 mPa.s.

**Solid contents:** approx. 100 %

### STORAGE CONDITIONS

At least 18 months after production. Limited shelf life after opening. Store in a dry, cool and frost free place.

### PRODUCT DESCRIPTION

Dual-component epoxy putty for permanent repair and restoration of wooden furniture and materials.

### FIELD OF APPLICATION

For repairing wood furniture, frames, stairs, boards, panels and toys. Fill cracks and holes. Can be used indoors and outdoors. Tip: Can also be used as a mouldable plug to fill screw holes.

### PROPERTIES

- Fast
- Paintable
- Easy to apply
- No shrinkage
- All-weather resistant
- Sandable

### PREPARATION

**Working conditions:** Use only at temperatures between +15°C and +25°C.

**Personal safety:** Preferably, process with gloves. After use, wash hands immediately and thoroughly with soap and water.

**Preliminary surface treatment:** The surface must be properly sanded and then cleaned and degreased.

**Tools:** A moist knife to cut off the required amount from the stick.

### APPLICATION

#### Directions for use:

Cut the required quantity from the rod with a damp knife (reinsert foil). Knead with your fingers until a homogeneous colour is obtained. If kneading is difficult, bring the rod at room temperature. Apply within 5-7 minutes after