



NASTRO BI-ADESIVO

EXTRA-STRONG DOUBLE-SIDED MOUNTING TAPE



PRODUCT DESCRIPTION

Extra-strong double-sided tape for permanently mounting and affixing objects in indoor areas. The simple alternative to screws and nails. Provides a permanent and secure hold on almost all smooth surfaces, e.g. metal, tiles, plastic, glass and painted wood. Ideal for mounting mirrors, holders, signs, hooks, shelving elements, cable channels, decorative objects, decorative profiles, and much more. Fully load-bearing after 60 minutes. Moisture-resistant.

FIELD OF APPLICATION

For quick, clean and easy mounting and fixing of objects like mirrors, soap dishes, suspension hooks, name plates, plastic holders, etc. on smooth and even surfaces indoors. Suitable for metal, tiles, plastic, glass, painted wood, etc. Ideal for use in sanitary rooms and kitchens. Not suitable for Application on rough surfaces (stone, decorative plaster) and vinyl wall covering.

PROPERTIES

- double-sided mounting tape
- extra-strong
- for smooth surfaces
- for indoor areas
- humidity resistant
- temperature resistant
- clean, easy, fast

PREPARATION

Working conditions: The minimum working temperature is 10°C.

Surface requirements: The surface must be clean, dry, free of dust and grease.

Preliminary surface treatment: For best results, first cleanse the surfaces to be glued (e.g. with alcohol or white spirit).

APPLICATION

Coverage: 2 cm per 350 g

Directions for use:

Stick the product onto the object to be mounted without creating air pockets. Remove the protective film without touching the adhesive. Affix the object to the desired spot and press hard. The object is fully load-bearing after only 60 minutes.

Stains/residue: Remove tape residue with white spirit.

Points of attention: Do not touch the adhesive as this reduces the tape's adhesive strength.

TECHNICAL PROPERTIES

Moisture resistance: Good

Chemicals resistance: Moderate

TECHNICAL SPECIFICATIONS

Chemical base: Foam with synthetic rubber

Colour: White

Specifications:

Liner: white silicone paper

Adhesive: synthetic rubber

Carrier: PE foam

Thickness without liner [µm]: 900

90° peel strength on steel (N/25 mm): 40

TEST CONDITIONS / EXECUTION

Adhesive strength depends on the quality of the surface as well as material and depth of the object; maximum adhesion determined through bonding flat metal objects (depth < 10 mm) on smooth and clean metal surfaces.

STORAGE CONDITIONS

At least 24 months after date of manufacture. Store in a dry, cool and frost free place.