

GOMMA LIQUIDA NASTRO EXCELLENT FOR (EMERGENCY) REPAIRS



Preliminary surface treatment: Ensure surfaces are as dry and clean as possible, remove any dust or grease. Because of the versatility of materials and conditions, it is recommended to do an adhesion test in advance.

TECHNICAL PROPERTIES

Moisture resistance: Very good **Water resistance:** Very good

Temperature resistance: -25°C - +70°C

TECHNICAL SPECIFICATIONS

Chemical base: Bitumen

Colour: Black

Thickness: approx. 1 mm Material top layer: PE

STORAGE CONDITIONS

Shelf life at least 24 months. Properly sealed packages should be stored in a dry, cool, frost-proof location at temperatures between $+5^{\circ}$ C and $+25^{\circ}$ C.

PRODUCT DESCRIPTION

Bostik Gomma Liquida® Nastro is excellent for (emergency) repairs. The tape is immediately water resistant and airtight, so you don't need to wait. The tape has a high adhesive strength and can even adhere to damp surfaces.

FIELD OF APPLICATION

Sealing, protecting and repairing virtually all materials, such as wood, concrete, stone, metal, zinc, bitumen, EPDM (pre-test), PVC, etc. Suitable for indoor and outdoor applications, such as bathrooms, roofs, cellars, walls and gardens. For immediate waterproofing of shower basins, floor seams, gutters, pipe conduits, window frames and skylight joints, ground level items, etc.

PROPERTIES

- Sealing, protecting and repairing
- Immediately 100% watertight
- 400% permanently elastic
- Adheres to virtually all materials
- High adhesive strength
- Even adheres to damp surfaces
- Can be used in combination with Bostik Gomma Liquida®
- High tear-bridging properties
- Resistant to temperatures between -25°C and +70°C.

PREPARATION

Working conditions: Only to be used at temperatures above $+5^{\circ}$ C. **Surface requirements:** Ensure surfaces are as dry and clean as possible, remove any dust or grease. Because of the versatility of materials and conditions, it is recommended to do an adhesion test in advance.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.