



METALLO LIQUIDO

LIQUID, FILLING METAL ADHESIVE.



Stains/residue: Remove the wet product with acetone. Cured adhesive residue can only be removed mechanically.

TECHNICAL PROPERTIES

Water resistance: Good

Filling capacity: Good

TECHNICAL SPECIFICATIONS

Colour: Grey

Viscosity: approx. Pasty

Solid matter: approx. 68 %

Density: approx. 1:1 g/cm³

STORAGE CONDITIONS

At least 24 months after date of manufacture. Limited shelf life after opening. Store tightly closed in a cool and frost-free place.

PRODUCT DESCRIPTION

Liquid, filling metal adhesive.

FIELD OF APPLICATION

repairs and sealing of metal surfaces. It fills the gaps between metal surfaces not perfectly fitting, for example for iron, steel, aluminium, lead and tin. For internal and external uses. Not suitable for -

PROPERTIES

- Filling capacity
- Water resistant
- Chemical-resistant
- After curing it can be ground, sanded, smoothed and painted
- With quick hardening
- Protects against rust formation

PREPARATION

Working conditions: Application temperature: between +5°C and +35°C.

Personal safety: -

Surface requirements: The materials to be glued must be dry, clean, rust-free and degreased.

Preliminary surface treatment: For optimal results, degrease first. Roughen smooth surfaces with sandpaper.

Tools: possibly a spatula or a brush for the application.

APPLICATION

Directions for use:

Apply directly and let it dry for 2-3 hours. To fill deep holes apply layer by layer.

When one layer is dry then apply the next one.