



# GOMMA LIQUIDA NASTRO

## EXCELLENT FOR (EMERGENCY) REPAIRS



### PRODUCT DESCRIPTION

Bostik Gomma Liquida® Nastro is excellent for (emergency) repairs. The tape is immediately water resistant and airtight, so you don't need to wait. The tape has a high adhesive strength and can even adhere to damp surfaces.

### FIELD OF APPLICATION

Sealing, protecting and repairing virtually all materials, such as wood, concrete, stone, metal, zinc, bitumen, EPDM (pre-test), PVC, etc. Suitable for indoor and outdoor applications, such as bathrooms, roofs, cellars, walls and gardens. For immediate waterproofing of shower basins, floor seams, gutters, pipe conduits, window frames and skylight joints, ground level items, etc.

### PROPERTIES

- Sealing, protecting and repairing
- Immediately 100% watertight
- 400% permanently elastic
- Adheres to virtually all materials
- High adhesive strength
- Even adheres to damp surfaces
- Can be used in combination with Bostik Gomma Liquida®
- High tear-bridging properties
- Resistant to temperatures between -25°C and +70°C.

### PREPARATION

**Working conditions:** Only to be used at temperatures above +5°C.

**Surface requirements:** Ensure surfaces are as dry and clean as possible, remove any dust or grease. Because of the versatility of materials and conditions, it is recommended to do an adhesion test in advance.

**Preliminary surface treatment:** Ensure surfaces are as dry and clean as possible, remove any dust or grease. Because of the versatility of materials and conditions, it is recommended to do an adhesion test in advance.

### APPLICATION

#### Directions for use:

Ensure surfaces are as dry and clean as possible, remove any dust or grease. Apply an overlapping layer if the surface is wider than the tape.

Temporary and emergency repairs: the tape can also be used on its own.

Permanent repairs: can be used in combination with Bostik Gomma Liquida®. Bostik Gomma Liquida® can be applied directly as soon as the circumstances and weather conditions allow. Minimum layer thickness: 2 mm after drying when used in combination with Bostik Gomma Liquida®.

### TECHNICAL PROPERTIES

**Moisture resistance:** Very good

**Water resistance:** Very good

**Temperature resistance:** -25°C - +70°C

### TECHNICAL SPECIFICATIONS

**Chemical base:** Bitumen

**Colour:** Black

**Thickness:** approx. 1 mm

**Material top layer:** PE

### STORAGE CONDITIONS

Shelf life at least 24 months. Properly sealed packages should be stored in a dry, cool, frost-proof location at temperatures between +5°C and +25°C.