



SUPER SIGILLANTE PITTORI

IMMEDIATELY PAINTABLE SEALANT WITHOUT THE RISK OF CRACKLING OR PAINT DISCOLOURATION.



PRODUCT DESCRIPTION

Superior, elasto-plastic, painter's-quality sealant based on acrylic dispersion for sealing joints, seams, crevices and cracks. The acrylic sealant can be painted over immediately after application, using any type of paint, without the risk of crackling (fine cracks/cracks in the paint) or discolouration of the paint.

FIELD OF APPLICATION

Suitable for joints, seams and cracks in ceiling and wall sockets, door and window frames, window sills, walls themselves, prefabricated elements, stairs, skirting boards, drywalls and conduits. Also suitable for sealing small cracks and cracks in walls. Adheres to bricks, (cellular) concrete, masonry, plasterwork, wood, glass, ceramic tiles, metal and rigid PVC. Does not adhere to bitumen, PE, PP, PTFE and silicone. For sealing window glass use Bostik Glazing Sealant. Not suitable for aquariums, bitumen, polyethylene (PE), polypropylene (PP), PTFE and silicone.

PROPERTIES

- Immediately paintable
- Does not craze
- No discolouration of the paint
- Particularly suitable for one-layer opaque paints (e.g. monodek®, powerdek®)
- Easy to tool for smooth results
- Clear white
- Can be used internally and externally
- UV and all-weather resistant
- Colourfast
- Sandable
- Non-corrosive to metals
- Permanently elasto-plastic (up to 12.5% stretch)

PREPARATION

Working conditions: Only apply at temperatures between +5°C and +40°C.

Surface requirements: The surface must be dry, clean and free of dust, rust and grease.

Preliminary surface treatment: For a better adhesion on porous (highly porous) substrates, they should be first covered with a diluted acrylic solution (1 part sealant to 2 parts water). For a good result, cover the joint's edges with masking tape. Ensure a minimum joint width of 6 mm. Up to a joint width of 12 mm, ensure a joint depth of 6 mm. In case of wider joint widths, the joint depth should be half the joint width. Remove masking tape immediately after tooling.

Tools: Apply cartridge contents with Bostik Click Gun. Multi Tool to open the cartridge and tooling the sealant.

APPLICATION

Coverage: Content suitable for approx. 8 to 15 m (depending on the diameter of the joint).

Directions for use:

Use sealant gun to handle cartridge. Open the cartridge by cutting off the plastic nipple on the top side at the screw thread with a sharp knife. Screw on the nozzle and chamfer at the desired width. For a good result, cover the joint's edges with masking tape. To prevent three-sided adhesion, fill deeper joints with a foam backer rod. Remove masking tape immediately after tooling and close cartridge. After 15 minutes, a surface skin will form. Curing 1 mm per 24 hours, depending on temperature and relative humidity. Immediately paintable after skin formation, for optimum result wait until fully cured.

Stains/residue: Remove wet stains immediately with water. Cured sealant residue can only be removed mechanically.

Points of attention: The crackling of the applied paint is restricted to a minimum due to the unique composition. Use Bostik Silicone Sealant in permanently damp areas.

TECHNICAL PROPERTIES

Moisture resistance: Good

Water resistance: Good

UV resistance: Good

Mildew resistance: Good

Elasticity: Good

Filling capacity: Good

TECHNICAL SPECIFICATIONS

Colour: White

Viscosity: approx. Pasty

Solid matter: approx. 84 %

Density: approx. 1.61 g/cm³

Shrinkage: approx. 17 %

Hardness (Shore A): approx. 35

100% modulus: approx. 0.4 MPa

STORAGE CONDITIONS

24 months Store in well-sealed packaging in a cool, dry and frost free place.