

# MONTAGGIO KIT ® SUPER RAPIDO NASTRO

# REMOVABLE AND STRONG MOUNTING TAPE.



#### **Directions for use:**

First mark all the corners of the object on the backside, because once objects are fixed it is practically impossible to move them without damaging the adhesive strips. Apply sufficient tape to the back of the object to mount (2 cm per 350 g). Remove the protective foil. Place the object in the right spot and press firmly. Removal: simply pull off the tape from the substrate. Leaves no residue. **Stains/residue:** Remove tape residue with white spirit.

# **TECHNICAL PROPERTIES**

Moisture resistance: Good **Chemicals resistance:** Moderate

#### STORAGE CONDITIONS

At least 24 months after date of manufacture.

# PRODUCT DESCRIPTION

Cleanly removable, powerful, two-sided adhesive assembly tape for smooth and flat interior surfaces. Ideal for the quick fixing of various objects.

# FIELD OF APPLICATION

For fast, strong, easy and temporary fixing of objects on flat and smooth surfaces (ceramic tiles, glass, metals, formica) indoors: mirrors, soap dishes, wall brackets, nameplates, plastic containers, posters etc. Ideal for use in washrooms. The tape is cleanly removable and therefore also very suitable for temporary fixing. Not suitable for Application on rough surfaces (stone, decorative plaster) and vinyl wall covering.

#### **PROPERTIES**

- · High bonding power: 350 g / 2 cm tape
- · Cleanly removable
- · Moisture resistant
- · Fast and easy
- · White

# **PREPARATION**

Working conditions: Apply to a substrate, which has approximately the same temperature as the tape and the surrounding area. For optimum adhesion apply tape at a temperature between  $+15^{\circ}$ C and  $+35^{\circ}$ C. To be processed at a relative humidity of 40-70%.

Surface requirements: Both parts must be dry, clean and free of dust and grease. One of the two parts must be porous (absorbent).

#### **APPLICATION**

Coverage: 2 cm per 350 g

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.