BIADESIVO INTERNI EXTRA-STRONG DOUBLE-SIDED MOUNTING TAPE



PRODUCT DESCRIPTION

Extra-strong double-sided tape for permanently mounting and affixing objects in indoor areas. The simple alternative to screws and nails. Provides a permanent and secure hold on almost all smooth surfaces, e.g. metal, tiles, plastic, glass and painted wood. Ideal for mounting mirrors, holders, signs, hooks, shelving elements, cable channels, decorative objects, decorative profiles, and much more. Fully load-bearing after 60 minutes. Moisture-resistant.

FIELD OF APPLICATION

For quick, clean and easy mounting and fixing of objects like mirrors, soap dishes, suspension hooks, name plates, plastic holders, etc. on smooth and even surfaces indoors. Suitable for metal, tiles, plastic, glass, painted wood, etc. Ideal for use in sanitary rooms and kitchens. Not suitable for applications outdoors and rough surfaces.

PROPERTIES

- · double-sided mounting tape
- extra-strong
- · for smooth surfaces
- · for indoor areas
- humidity resistant
- · temperature resistant
- · clean, easy, fast

PREPARATION

Working conditions: The minimum working temperature is 10°C. **Surface requirements:** The surfaces to be glued must be firm, clean, dry, and free of grease and dust. **Preliminary surface treatment:** For best results, first cleanse the surfaces to be glued (e.g. with alcohol or white spirit).

APPLICATION

Directions for use:

Stick the product onto the object to be mounted without creating air pockets. Remove the protective film without touching the adhesive. Affix the object to the desired spot and press hard. The object is fully load-bearing after only 60 minutes.

Stains/residue: Remove tape residue with white spirit.

Points of attention: Do not touch the adhesive as this reduces the tape's adhesive strength.

CURE TIMES*

Final bonding strength after: approx. 60 minutes

* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

TECHNICAL PROPERTIES

Moisture resistance: Good Temperature resistance: -10°C to +75°C

TECHNICAL SPECIFICATIONS

Appearance: white **Specifications:** Liner: white silicone paper Adhesive: synthetic rubber Carrier: PE foam Thickness without liner [μm]: 900 90° peel strength on steel (N/25 mm): 40

TEST CONDITIONS / EXECUTION

Adhesive strength depends on the quality of the surface as well as material and depth of the object; maximum adhesion determined through bonding flat metal objects (depth < 10 mm) on smooth and clean metal surfaces.

STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

PACK SIZES

Tape: 1.5 m x 19 mm on blistercard Strips: 16 pieces in wallet

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.

65665 2

202010