

STEX® ES/PT/RO/EL UNCLOGGING PEARLS WITH ALUMINIUM COATING



PRODUCT DESCRIPTION

Unclogging pearls with aluminium coating.

FIELD OF APPLICATION

For removing clogging and unpleasant odours caused by, for example, hair, soap, oil, grease and food residue in drains of kitchen sinks, wash basins, showers and bath tubs in bathrooms, kitchen and toilet. Suitable for materials including synthetics (PVC, PVCC, ABS, Acrylic), enamel, porcelain and metals (copper, stainless steel, chrome, iron) with the exception of aluminium. Also suitable for preventive use.

PROPERTIES

- $\cdot \, Fast$
- · Effective
- · Simple to use
- · With aluminium coating
- $\cdot \ \text{With convenient vermiculite} \\$
- · Does not affect PVC and metal (except aluminium)
- · Childproof closure

APPLICATION

Directions for use:

Remove as much water as possible from the drain. For preventive maintenance, administer half a cap in the drain and add a cup of water. Watch out for splashes! Let soak for a few minutes and then thoroughly flush the drain, preferably with warm water. When clogged, administer a full cap in the drain and add two cups of water. Let soak for a few minutes and then thoroughly flush the drain, preferably with warm water. Once the drain is running again, administer half a cap in the drain and add a cup of water. Let soak for a few minutes and then thoroughly flush the drain. Properly close the container immediately after use.

Points of attention: Provide adequate ventilation during usage. During use a fast, effervescent reaction will take place, whereby the temperature can rise considerably to about 100°C at a mixing ratio of 1:1 with water at 20°C. Watch out for splashes! Properly close the container immediately after use.

TECHNICAL SPECIFICATIONS

Chemical base: Sodium hydroxide (caustic soda) granules coated with

aluminium **Colour:** Grey

Density: approx. 2.1 g/cm³

STORAGE CONDITIONS

At least 24 months after date of manufacture. Close the container properly and store in a dry, cool and frost-free location.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.